


AGC010

✉ sales@brannan.co.uk

☎ +44 (0)1946 816600

🌐 brannan.co.uk

Pressure gauge cock



Product features:

- Allows gauge to be isolated from pressure medium to protect against gauge failure
- Allows gauge to be removed for servicing
- To DIN16261 PN16
- Available with or without vent hole
- Other connections available on request

Applications:

- Heating, ventilation, air-conditioning
- Hot water
- Industrial

Standard product specifications:

Standard	DIN 16261 : 2004-7
Connection	BSP or NPT (others available on request)
Wetted parts	Brass, CZ121 / CW614N (steel or stainless steel on request)
Handle	Black plastic
Vent hole	With or without
Maximum pressure	16 bar
Operating temperature	Ambient: -20 to +50°C Medium: -20 to +50°C
Storage temperature	-40 to +60°C

Standard product numbers:

BSP Connection	Product number	
	Standard	With vent hole
3/8" BSP F & F	39/001/0	39/001/9
1/2" BSP F & F	39/003/0	39/003/9
1/4" BSP F & F	39/008/0	39/008/9
1/4" BSP M & F	39/200/0	39/200/9
3/8" BSP M & F	39/202/0	39/202/8
1/2" BSP M & F	39/203/0	39/202/9

NPT Connection	Product number	
	Standard	With vent hole
3/8" NPT F & F	39/207/0	39/207/9
1/2" NPT F & F	39/003/4	39/003/5
1/4" NPT F & F	39/206/0	39/206/9
1/4" NPT M & F	39/208/0	39/208/9
3/8" NPT M & F	39/209/0	39/209/9
1/2" NPT M & F	39/203/4	39/203/5

Net weights	*Gross weights
130g	141.5g
187g	198.5g
117g	128.5g
117g	128.5g
130g	141.5g
187g	198.5g

* Supplied in individual box

Box weight: 11.5g

Box dimensions: 150 x 60 x 30mm

View me on
the website



REV0.2026

Measurement for life.

