Product data sheet

C € \overline{k}

MINI THERMO-SOUND LEVEL METER

Easy to use sound level meter as part of our range of mini environmental meters.

Product features:

- High accuracy, fast response
- Sound level and temperature measurement
- Wide frequency range
- Over range indication
- Auto power off enable/disable function
- Supplied with 3 point Calibration Certificate
- Colour LCD display with backlight
- MAX/MIN and data hold
- Fast/slow time weighting
- Low battery indication
- CE & RoHS/WEEE Compliant



Measurement	Range			Accuracy	Resolution
Temperature:	-20 to +70°C&F			+/- 1.5°C (2.7°F)	0.1°C&F
Sound Level:	35 to 13	35 dB		+/- 2.0 dB	0.1
Dynamic Range:		50 dB			
Frequency Range:		31.5 to 8	8 KHz		
Frequency Weighting:		А			
Time Weighting:		Fast: 125 ms / Slow: 1s			
Data Update:		300 ms			
Microphone:		1/2" electrets condenser			
High/Low Reading Indication:		> 100 dB: LCD displays "Hi" / < 100 dB: LCD displays "LO"			
Power Off:		Auto shut down after 15 mins inactivity (unless auto off disabled)			
Operating Conditions:		-20 to +60°C&F / 10 to 90%RH			
Storage Conditions:		-20 to +60°C&F / 10 to 75%RH			
Battery:		3 x AAA (included)			
		Average life - 60 hours on continuous use			
Dimensions:		LCD:	30 x 28m	m	
		Net:	144 x 56	x 30.5mm	
		Gross:	247 x 130) x 43mm	
Weight:		Meter:		ncluding batteries)	
		Paper:	19g (card	l, instructions & certificate)
		Blister:	34g		
		Gross:	153.5g		

Description	Barcode	Product no
Mini Thermo-Sound Level Meter	5 011405 134714	13/471/0

Sound Level Motor





View me on





