

## **Product data sheet**



+44 (0)1946 816600



## VERTICAL BARREL TEST THERMOMETER

Electronic test thermometer with vertical display and 125mm stainless steel probe with pocket case and clip. Probe thermometers can be supplied with UKAS calibration certificate or statement of conformity on request.

Packed in individual box with battery and full operating instructions.

## **Product features:**

- · Stainless steel probe
- · Protective case and pocket clip
- · Battery and full instructions included

## **Product specifications:**

Temperature range: -50 to +200°C/°F

Ambient temperature: -10 to +50°C/°F

-50 to -21°C: +/-4°C

-20 to -1°C: +/-2°C

0 to 100°C: +/-2°C 101 to 150°C: +/-2°C 151 to 200°C: +/-4°C

Recommended minimum

immersion length: 50mm\*
Resolution: 0.1°C
Sampling rate: 1 second

Auto power off:After 45 minutesBattery:LR44 x 1 pcAverage battery life:Approx 1500 hours

CE/ROHS/WEEE: Compliant

**Hazard information (SDS):** See brannan.co.uk for information

LCD dimensions: 18mm x 8mm

**Probe dimensions:** 125mm x ø3.75mm (reducing to ø2.5mm)

**Product dimensions:** Net: 195mm x 21mm x 21mm

Gross: 230mm x 25mm x 25mm

**Product weight:** Net: 21g (including battery)

Display box: 10.5g Gross: 31.5g

Description	Barcode	Product no
Vertical barrel test thermometer	5 011405 311603	31/160/0

<sup>\*</sup> The thermometers will operate at shorter immersions, however the stated accuracy cannot be maintained.





View me on the website



