THERM-*cert*™ range **Product data sheet**





+44 (0)1946 816600



PRE-CALIBRATED FOLDING PROBE THERMOMETER

High accuracy thermometer pre-calibrated at two fixed temperature points and part of the Brannan **THERM**-cert[™] range.

Foldable thermometer with stainless steel sensor probe, adjustable from 0 to 180 degrees, to allow different angle viewing. The probe folds away conveniently for easy storage when not in use. Suitable for a variety of uses including HVAC, food processing, agriculture, laboratory and energy management.



High accuracy thermometer supplied with traceable calibration certification

Foldable probe for convenient use and easy storage

Stainless steel probe adjusts from 0° to 180°

Protection to IP 65

One second temperature sensing time

Auto power on when probe is opened more than 30° angle

Auto power off when probe is closed less than 30° angle

Wrist strap and battery included

Product specifications:

-50 to +250°C/°F (switchable) Temperature range: -50 to -21°C: +/- 4°C (8°F) Accuracy: -20 to -1°C: +/- 1.5°C (3°F) 0 to +100°C: +/- 1°C (2°F)

101 to 150°C: +/- 1.5°C (3°F) 151 to 200°C: +/- 4°C (8°F) 201 to 250°C: +/- 5%

2 points @ 0 and 90°C

Calibration:

Sample rate: 1 second Resolution: 0.1°C **Battery:** LR44 x 1 pc CE/ROHS/WEEE: Compliant

See brannan.co.uk for information Hazard information (SDS):

LCD dimensions: 15mm x 32mm Probe dimensions: 85mm x ø3.5mm

Product dimensions: Net: 45mm x 125mm x 18mm (with probe closed)

Gross: 275mm x 240mm x 37mm

Product weight: Net: 50g (incl. battery & wrist strap)

Display box: 12g

Gross: 78g (incl. certificate and packaging)

Brannan England	24.7c Hold
ficate	

ISSUED BY : S.Brannan and Sons Limited					
CALIBRATION DATE	CEI	CERTIFICATE NUMBER		SERIAL NUMBER	
S. Brannan and Sonds Ltd. Leconfield Industrial Estate Cleator Moor Cumbria ENGLAND CA25 6QE		Brannan Thermometers and Gauges	Telephone: +44 (0) 194831666 Fax: +44 (0) 194881662 E Mail: sales@brannan.co. Web: www.brannan.co. Registere No: 290812 ENGLAN		
Instrument Type:	ELECTRONIC T	HERMOMETER			
Range:	-50/250°C&F	•	Y	4	
Resolution:	0.1°C				
Immersion:	76mm	~) \			
	90.0	N/A N/A	246801/1 246801/1	246801/3 246801/3	
Signed: S. Moran		libration Assistant and Approved S Laboratory Humidity 2		MINES SO	





