

Product data sheet

AGC040 - STAINLESS STEEL GAUGE COCKS

Product features:

- Allows gauge to be isolated from pressure medium to protect against gauge failure
- Allows gauge to be removed for servicing

Design:

- Max pressure 100 bar
- Available with or without vent hole
- Other connections available on request

Applications:

- Heating, ventilation, air-conditioning
- Hot water
- Industrial

Standard product specifications:

Connection	BSP or NPT
Wetted parts	SS 304 / SS 316
Handle	Black plastic
Maximum pressure	100 bar
Operating temperature	Ambient: -20 to +60°C Medium: -20 to +180°C
Storage temperature	-40 to +60°C

Standard product numbers:

Stainless steel 304

Connection	BSP connection		NPT connection	
	Standard	With vent hole	Standard	with vent hole
1/4" Female x Female	39/070/0	39/070/9	39/070/4	39/070/5
1/4" Male x Female	39/071/0	39/071/9	39/071/4	39/071/5
3/8" Female x Female	39/072/0	39/072/9	39/072/4	39/072/5
3/8" Male x Female	39/073/0	39/073/9	39/073/4	39/073/5
1/2" Female x Female	39/074/0	39/074/9	39/074/4	39/074/5
1/2" Male x Female	39/075/0	39/075/9	39/075/4	39/075/5

Standard product numbers:

Stainless steel 316

Connection	BSP connection		NPT connection	
	Standard	With vent hole	Standard	with vent hole
1/4" Female x Female	39/080/0	39/080/9	39/080/4	39/080/5
1/4" Male x Female	39/081/0	39/081/9	39/081/4	39/081/5
3/8" Female x Female	39/082/0	39/082/9	39/082/4	39/082/5
3/8" Male x Female	39/083/0	39/083/9	39/083/4	39/083/5
1/2" Female x Female	39/084/0	39/084/9	39/084/4	39/084/5
1/2" Male x Female	39/085/0	39/085/9	39/085/4	39/085/5

