## **Product data sheet**





+44 (0)1946 816600



# HEAVY DUTY WIND SPEED METER (ANEMOMETER) WITH THERMOMETER & HUMIDITY METER

#### Factory Calibration Certificate Included

#### **Product features:**

- Air velocity and air volume measurement with temperature and humidity meter
- · Large LCD with green, yellow and red light indication
- Supplied with calibration certificate in sturdy protective pouch
- · Air velocity level indication
- Max min / AVG / data hold functions
- · Low battery indication
- · Audible alarm
- · Auto power off

#### **Product specifications:**

Air velocity specifications:

**Measuring range:** 0.4 to 35 m/s, 1.4 to 122.5 km/hr

78.9 to 6889.6 ft/min, 0.77 to 68 knots

0.89 to 78.2 Mph

150 to 10500 CMM (cubic meter per minute) 692.9 to 55117.4 CFM (cubic feet per minute)

**Accuracy:** +/- 3% of reading

**Resolution:** 0.1m/s

**Level indication:** 3-colour LED light alarm

Audible alarm: Alarm sounds for 20 seconds, pauses for 1 minute

then repeats cycle. (The audible alarm defaults to

ON state and can be turned off by user)

**Area set:**0.1 to 9999 CM²/0.1 to 9999 M²/0.1 to 9999ft² **Overrange indication:**"OL" displayed when wind speed exceeds 40m/s

Temperature specifications:

Range: -30 to 60°C (-22 to 140°F)

**Accuracy:** +/-1.5°C (+/-2.7°F)

Apparent ("feels like") range: -20 to 60°C (-4 to 140°F)

Apparent ("feels like") accuracy: +/-1°C (+/-1.8°F)
Resolution: 0.1°C/F

**Humidity specifications:** 

Range: 10 to 100%RH

Accuracy: ±5%RH between 35 and 75%RH, otherwise±7%RH

Resolution: 1%RH









### sales@brannan.co.uk

## **Product data sheet**





#### General instument specifications:

AVG: Average of the latest 10 readings

Overloading display: Display "LO" under range and "HI" over range

**Operating conditions:**  $-20 \text{ to } 60^{\circ}\text{C} \text{ (-4 to } 140^{\circ}\text{F)} < 90\%\text{RH (non-condensing)}$ 

Storage conditions: $-30 \text{ to } 60^{\circ}\text{C} \text{ (-22 to } 140^{\circ}\text{F)} < 80\%\text{RH}$ Auto power offAfter approx. 15 minutes of inactivityBattery: $3 \times AA \text{ batteries or USB type-C cable}$ 

Battery life: Min. 30 hours
CE & RoHS/WEEE: Compliant
LCD dimensions: 55mm x 48mm

**Product dimensions:** Net: 231mm x 68mm x 30mm

Gross: 265mm x 85mm x 48mm

**Product weights:** Meter: 254g

Protective pouch: 45g

Box & instruction sheet: 57.5g

Gross: 357g

Description	Barcode	Product no
Heavy duty thermo-anemometer	5 011405 13/4905	13/490/0

